

Application S/N 10/820,920  
Amendment Dated: October 13, 2005

CE12122JUI

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (currently amended) An apparatus for indication of a charging condition, comprising:

an indication circuit having at least one electromagnet; and

a charge control circuit for controlling charging current to a power supply of a portable device;

wherein the indication circuit causes the apparatus to electromagnetically engage the portable device and the charge control circuit provides charging current to the power supply of the portable device during the engagement and wherein the indication circuit causes the apparatus to electromagnetically decouple the portable device when the power supply of the portable device is charged to a predetermined level to permit a user to remove the portable device from the apparatus.

2. (original) The apparatus according to claim 1, wherein the apparatus further comprises at least one contact and wherein the apparatus contact electrically couples to a contact of the portable device when the apparatus electromagnetically engages the portable device.

Application S/N 10/820,920  
Amendment Dated: October 13, 2005

CE12122JUI

3. (currently amended) The apparatus according to claim 1, wherein the indication circuit provides an engaging current to the electromagnet, wherein the engaging current causes the electromagnet to generate ~~at least one of~~ an attractive magnetic field ~~and~~ or a repulsive magnetic field.

4. (currently amended) The apparatus according to claim 3, wherein when the electromagnet generates an attractive magnetic field, the electromagnet attracts at ~~least one of~~ a non-magnetized, metallic component of the portable device ~~and~~ or an opposite pole magnet of the portable device.

5. (original) The apparatus according to claim 3, wherein when the electromagnet generates a repulsive magnetic field, the electromagnet repels a like pole magnet of the portable device.

6. (original) The apparatus according to claim 2, wherein the electromagnet and the contacts are positioned on a first surface of the apparatus.

7. (original) The apparatus according to claim 2, wherein the electromagnet is positioned on a first surface of the apparatus and the contacts are positioned on a second surface of the apparatus, wherein the second surface opposes the first surface.

Application S/N 10/820,920  
Amendment Dated: October 13, 2005

CE12122JUI

8. (currently amended) The apparatus according to claim 1, wherein the electromagnet generates a magnetic field when the apparatus electromagnetically engages the portable device and the magnetic field decreases in strength as the power supply of the portable device is charged towards the predetermined level.

9. (original) The apparatus according to claim 8, wherein the indication circuit and the charge control circuit are in series.

10. (currently amended) The apparatus according to claim 1, wherein the electromagnet generates a magnetic field when the apparatus electromagnetically engages the portable device and the magnetic field remains at a substantially fixed level as the power supply of the portable device is charged towards the predetermined level.

11. (original) The apparatus according to claim 10, wherein the indication circuit and the charge control circuit are in parallel.

12. (original) The apparatus according to claim 1, wherein the apparatus further comprises a sensor for determining whether the portable device has been removed from the apparatus.

Application S/N 10/820,920  
Amendment Dated: October 13, 2005

CE12122JUI

13. (currently amended) An apparatus for indication of a charging condition, comprising:

an indication circuit having at least one electromagnet; and

a charge control circuit for controlling charging current to a power supply of a portable device;

wherein the indication circuit causes the apparatus to electromagnetically engage the portable device in a first position and the charge control circuit provides charging current to the power supply of the portable device during the first position engagement and wherein the indication circuit causes the apparatus to electromagnetically engage the portable device in a second position when the power supply of the portable device is charged to a predetermined level such that a user is permitted to remove the portable device from the apparatus.

14. (currently amended) A portable device, comprising:

a power supply;

at least one contact for electrically coupling to at least one corresponding contact on a charging unit; and

a magnetically susceptible component;

wherein the charging unit electromagnetically engages the magnetically susceptible component and provides a charging current to the power supply of the portable device through the contacts of the portable device and the corresponding contacts of the charging unit during the engagement;

Application S/N 10/820,920  
Amendment Dated: October 13, 2005

CE12122JUI

wherein the charging unit electromagnetically decouples the portable device when the power supply of the portable device is charged to a predetermined level to permit a user to remove the portable device from the charging unit.

15. (currently amended) The portable device according to claim 14, wherein the magnetically susceptible component is ~~at least one of~~ a non-magnetized, metallic component ~~and~~ or a magnet.

16. (original) The portable device according to claim 15, wherein the magnet of the portable device is a like pole magnet with respect to an electromagnet in the charging unit such that the electromagnet generates a repulsive magnetic field when the charging unit electromagnetically engages the portable device.

17. (currently amended) A method for indication of a charging condition, comprising the steps of:

electromagnetically engaging a portable device to a charging unit such that the portable device is magnetically urged towards and secured to at least a portion of the charging unit;

supplying charging current to a power supply of the portable device; and  
when the power supply of the portable device is charged to a predetermined level, electromagnetically decoupling the portable device from the charging unit to permit a user to remove the portable device from the charging unit.

Application S/N 10/820,920  
Amendment Dated: October 13, 2005

CE12122JUI

18. (currently amended) The method according to claim 17, further comprising the steps of:

providing an engaging current to at least one electromagnet of the charging unit, wherein the providing an engaging current step causes the electromagnet to generate ~~at least one of~~ an attractive magnetic field ~~and or~~ a repulsive magnetic field.

19. (currently amended) The method according to claim 17, wherein the charging unit has at least one electromagnet and the method further comprises the steps of:

generating a magnetic field during the electromagnetically engaging step;

and

decreasing the strength of the magnetic field as the power supply of the portable device is charged towards the predetermined level.

20. (currently amended) The method according to claim 17, wherein the charging unit has at least one electromagnet and the method further comprises the steps of:

generating a magnetic field during the electromagnetically engaging step;

and

keeping the strength of the magnetic field at a substantially constant level as the power supply of the portable device is charged towards the predetermined level.

Application S/N 10/820,920  
Amendment Dated: October 13, 2005

CE12122JUI

21. (currently amended) The method according to claim 17, further comprising the steps of [[:]] :

determining whether the portable device has been removed from the charging unit; and

in response to the portable device being removed from the charging unit, setting the charging unit to a predetermined charging configuration.

22. (original) The method according to claim 17, wherein the electromagnetically engaging step comprises magnetically urging and securing the portable device to the charging unit with an attractive magnetic field and the electromagnetically decoupling step comprises removing the attractive magnetic field.

23. (original) The method according to claim 17, wherein the electromagnetically engaging step comprises magnetically urging and securing the portable device to the charging unit with a repulsive magnetic field and the electromagnetically decoupling step comprises removing the repulsive magnetic field.

Application S/N 10/820,920  
Amendment Dated: October 13, 2005

CE12122JUI

24. (currently amended) A method for indication of a charging condition, comprising the steps of:

electromagnetically engaging a portable device to a charging unit in a first position such that the portable device is magnetically urged towards and secured to at least a first portion of the charging unit;

supplying charging current to a power supply of the portable device; and

when the power supply of the portable device is charged to a predetermined level, electromagnetically engaging the portable device to the charging unit in a second position such that the portable device is magnetically urged towards and secured to a second portion of the charging unit, wherein when the portable device is in the second position, a user is permitted to remove the portable device from the charging unit.